

# GT303

Cable **People**  
for Cable **Makers**

## Technical Data Sheet

Bedding, Binding & Barrier Tape

**GECA-TAPES**

Non-conductive polyester nonwoven tape for binding and separation with high flexibility and easy processing.

### Applications

- Separation inside specialty cables and low voltage cables
- General binding applications

### Characteristics

- Colour: white
- Traverse wound spool available

### Type of Cable

- Control cable
- Data cable
- Specialty cable

### Product Information

Typical Properties (T = 23°C - RH = 50%)	GT303	Test Method
Mass Per Unit Area (g/m <sup>2</sup> )	25	ISO-9073-1
Thickness (mm)	0.04	ISO-9073-2
Tensile Strength (N/cm)	14	ISO-9073-3
Elongation (%)	13	ISO-9073-3
Maximum Processing Temperature (°C)	230	GTEST12*
Maximum Service Temperature (°C)	90	IEC-216

\*Geca-Tapes Test Method



Light Weight



Reduced Thickness



Extreme Flexibility

When ordering, please specify slit width, inner diameter and maximum outside diameter.

+33 (0) 3 28 43 74 74    info@geca-tapes.com    geca-tapes.com

PGI Geca-Tapes, ZI de la Blanche Maison, Avenue des Nations Unies, BP 109, 59270 Bailleul, France

A Brand of  
**Berry**