

GT403

Cable **People**
for Cable **Makers**

Technical Data Sheet

Bedding, Binding & Barrier Tape

GECA-TAPES

Non-conductive polyester nonwoven tape for bedding, binding and separation with scrim reinforcement for added strength.



Excellent Binding

Applications

- High strength binding of cable components
- Separation of cable components

Characteristics

- Colour: white
- Traverse wound spool available

Type of Cable

- High voltage cable
- Marine power cable
- Marine umbilical cable



Scrim Reinforcement

Product Information

Typical Properties (T = 23°C - RH = 50%)	GT403	Test Method
Mass Per Unit Area (g/m ²)	110	ISO-9073-1
Thickness (mm)	0.15	ISO-9073-2
Tensile Strength (N/cm)	110	ISO-9073-3
Elongation (%)	14	ISO-9073-3
Maximum Processing Temperature (°C)	230	GTEST12*
Maximum Service Temperature (°C)	145	IEC-216



Reduced Thickness

*Geca-Tapes Test Method

When ordering, please specify slit width, inner diameter and maximum outside diameter.

+33 (0) 3 28 43 74 74 info@geca-tapes.com geca-tapes.com

PGI Geca-Tapes, ZI de la Blanche Maison, Avenue des Nations Unies, BP 109, 59270 Bailleul, France

A Brand of
Berry