

GTC2830

Cable **People**
for Cable **Makers**

Technical Data Sheet

Semi-Conductive Water Blocking Tape

GECA-TAPES

Semi-conductive TopSwell polyester tape, with high performance water blocking properties and great flexibility for easy processing.

Applications

- General water blocking of open spaces inside all power cables
- Longitudinal water blocking of screen area of medium voltage cables

Characteristics

- Colour: black
- Traverse wound spool available

Type of Cable

- Medium voltage cable
- High voltage cable

Product Information

Typical Properties (T = 23°C - RH = 50%)	GTC2830	Test Method
Mass Per Unit Area (g/m ²)	93	ISO-9073-1
Thickness (mm)	0.4	ISO-9073-2
Tensile Strength (N/cm)	30	ISO-9073-3
Elongation (%)	14	ISO-9073-3
Swelling Speed (mm/1'00'')	8	GTEST20*
Swelling Height (mm/3'00'')	12	GTEST20*
Maximum Processing Temperature (°C)	230	GTEST12*
Maximum Service Temperature (°C)	90	IEC-216
Surface Resistance (Ω/□)	1500	IEC-167
Volume Resistance (MΩ.cm)	0.5	DIN-54345

*Geca-Tapes Test Method

When ordering, please specify slit width, inner diameter and maximum outside diameter.

+33 (0) 3 28 43 74 74 info@geca-tapes.com geca-tapes.com

PGI Geca-Tapes, ZI de la Blanche Maison, Avenue des Nations Unies, BP 109, 59270 Bailleul, France



Excellent
Swelling Height



Rapid Swelling
Speed



Proven Long
Term Stability

A Brand of
Berry