

# GT1030

Cable **People**  
for Cable **Makers**

## Technical Data Sheet

Non-Conductive Water Blocking Tape

**GECA-TAPES**

Non-conductive TopSwell polyester tape, with high performance water blocking properties and great flexibility for easy processing.

### Applications

- Longitudinal water blocking inside conductor and screen area
- General water blocking of open spaces inside all power, telecom or special cables

### Characteristics

- Colour: white
- Traverse wound spool available

### Type of Cable

- Medium voltage cable
- High voltage cable
- Fiber optic cable

### Product Information

Typical Properties (T = 23°C - RH = 50%)	GT1030	Test Method
Mass Per Unit Area (g/m <sup>2</sup> )	83	ISO-9073-1
Thickness (mm)	0.33	ISO-9073-2
Tensile Strength (N/cm)	38	ISO-9073-3
Elongation (%)	10	ISO-9073-3
Swelling Speed (mm/1'00")	8	GTEST20*
Swelling Height (mm/3'00")	12	GTEST20*
Maximum Processing Temperature (°C)	230	GTEST12*
Maximum Service Temperature (°C)	90	IEC-216

\*Geca-Tapes Test Method

When ordering, please specify slit width, inner diameter and maximum outside diameter.

+33 (0) 3 28 43 74 74    info@geca-tapes.com    geca-tapes.com

PGI Geca-Tapes, ZI de la Blanche Maison, Avenue des Nations Unies, BP 109, 59270 Bailleul, France



Proven Long Term  
Stability



Rapid Swelling  
Speed



Excellent Swelling  
Height