

Technical Data Sheet

Bedding, Binding & Barrier Tape

GECA-TAPES

Semi-conductive polyester nonwoven bedding tape, for longitudinal water blocking and with scrim reinforcement for added strength.

Applications

- High tensile conductor wrapping with water blocking feature
- Semi-conductive wrapping applications in energy cables where longitudinal water blocking is required

Characteristics

- Colour: black
- Traverse wound spool available

Type of Cable

- Medium voltage cable
- High voltage cable

Product Information

Typical Properties (T = 23°C - RH = 50%)	GTS608	Test Method
Mass Per Unit Area (g/m ²)	150	ISO-9073-1
Thickness (mm)	0.38	ISO-9073-2
Tensile Strength (N/cm)	110	ISO-9073-3
Elongation (%)	15	ISO-9073-3
Swelling Speed (mm/1'00")	3	GTEST20*
Swelling Height (mm/3'00")	7,0/10'00"	GTEST20*
Maximum Processing Temperature (°C)	230	GTEST12*
Maximum Service Temperature (°C)	90	IEC-216

*Geca-Tapes Test Method

When ordering, please specify slit width, inner diameter and maximum outside diameter.

+33 (0) 3 28 43 74 74 info@geca-tapes.com geca-tapes.com

PGI Geca-Tapes, ZI de la Blanche Maison, Avenue des Nations Unies, BP 109, 59270 Bailleul, France



FreeSwell
Direct Swelling



Scrim Reinforcement



Excellent Binding

A Brand of
Berry